
hansgrohe

EN Instructions for use / Assembly instructions 2
DE Gebrauchsanleitung / Montageanleitung 3



Bidette 1jet S EcoSmart
29234000 / 29244000



Bidette 1jet S EcoSmart
29238XX0

Safety Notes

- Gloves should be worn during installation to prevent crushing and cutting injuries.
- The product may only be used for bathing, hygienic and body cleaning purposes.
- Do not allow the streams of the shower touch sensitive body parts (such as your eyes). An adequate distance must be kept between the shower and you.

Installation Instructions

- Prior to installation, inspect the product for transport damages. After it has been installed, no transport or surface damage will be honoured.
- The pipes and the fixture must be installed, flushed and tested as per the applicable standards.
- The plumbing codes applicable in the respective countries must be observed.
- To avoid cross flow, connect the shower only to check valves, to the sanitary fittings specifically provided for this purpose, or to fittings with integrated backflow preventers in the water connections.
- The premounted dirt collection screen must be used to prevent dirt from entering through the pipes. Dirt entering can affect the function and/or lead to damage to the functional components of the fitting. Hansgrohe will not be held liable for any resulting damage.

Technical Data

Operating pressure:	max. 1 MPa
Recommended operating pressure:	0,1 - 0,5 MPa
Test pressure:	1,6 MPa (1 MPa = 10 bar = 145 PSI)
Hot water temperature:	max. 60 °C
Thermal disinfection:	70 °C / 4 min

- The product is exclusively designed for drinking water!
- Not intrinsically safe against backflow
- Not suitable for operation in countries where EN 1717 is valid

Symbol description

Do not use silicone containing acetic acid!

Dimensions (see page 6)

Flow diagram (see page 6)

Spare parts (see page 7)

XX - Colors
00 - Chrome Plated
14 - Brushed Bronze
34 - Brushed Black Chrome
67 - Matt Black
70 - Matt White
99 - Polished Gold-Optic

Maintenance (see page 8)

The check valves must be checked regularly according to EN 806-5 in accordance with national or regional regulations (at least once a year).

Cleaning (see page 7)

Operation (see page5)

Assembly (see page 4)

Sicherheitshinweise

- Bei der Montage müssen zur Vermeidung von Quetsch- und Schnittverletzungen Handschuhe getragen werden.
- Das Produkt darf nur zu Bade-, Hygiene- und Körperreinigungszwecken eingesetzt werden.
- Der Kontakt der Brausestrahlen mit empfindlichen Körperstellen (z. B. Augen) muss vermieden werden. Es muss ein ausreichender Abstand zwischen Brause und Körper eingehalten werden.

Montagehinweise

- Vor der Montage muss das Produkt auf Transportschäden untersucht werden. Nach dem Einbau werden keine Transport- oder Oberflächenschäden anerkannt.
- Die Leitungen und die Armatur müssen nach den gültigen Normen montiert, gespült und geprüft werden.
- Die in den Ländern jeweils gültigen Installationsrichtlinien sind einzuhalten.
- Um Kreuzfluss zu vermeiden, darf die Brause nur an Absperrventile, speziell dafür vorgesehene Sanitärarmaturen oder Armaturen mit integrierten Rückflussverhindereren in den Wasseranschlüssen angeschlossen werden.
- Das vormontierte Schmutzfangsieb muss verwendet werden, um Schmutzeinspülungen aus dem Leitungsnetz zu vermeiden. Schmutzeinspülungen können die Funktion beeinträchtigen und/oder zu Beschädigungen an Funktionsteilen der Armatur führen. Für hieraus ergebende Schäden haftet Hansgrohe nicht.

Technische Daten

Betriebsdruck:	max. 1 MPa
Empfohlener Betriebsdruck:	0,1 - 0,5 MPa
Prüfdruck:	1,6 MPa (1 MPa = 10 bar = 145 PSI)
Heißwassertemperatur:	max. 60 °C
Thermische Desinfektion:	70 °C / 4 min

- Das Produkt ist ausschließlich für Trinkwasser konzipiert!
- Nicht ausreichend gegen Rückfließen
- Nicht geeignet für Betrieb in Ländern mit gültiger EN 1717

Symbolerklärung

Kein essigsäurehaltiges Silikon verwenden!

Maße (siehe Seite 6)

Durchflussdiagramm (siehe Seite 6)

Servicateile (siehe Seite 7)

XX – Farbcodierung
00 – Chrom
14 – Brushed Bronze
34 – Brushed Black Chrome
67 – Mattschwarz
70 – Mattweiß
99 – Polished Gold-Optic


Wartung (siehe Seite 8)


Rückflussverhindereer müssen gemäß EN 806-5 regelmäßig in Übereinstimmung mit nationalen oder regionalen Bestimmungen auf ihre Funktion geprüft werden (mindestens einmal jährlich).


Reinigung (siehe Seite 7)


Bedienung (siehe Seite5)

Montage (siehe Seite 4)



1a


1b



2a
Silicone
Ø 6



2b
Silicone
25
Ø 6



1.


2.



3.


1.



2.


3.


Bidette 1jet S EcoSmart
29234000




Bidette 1jet S EcoSmart
29244000



Bidette 1jet S EcoSmart
29238XX0





www.hansgrohe.com/cleaning-recommendation













EN Cleaning recommendation / Warranty / Contact


DE Reinigungsempfehlung / Garantie / Kontakt














hansgrohe
Hansgrohe · Auestraße 5 - 9 · D-77761 Schiltach · Telefon +49 (0) 7836511-1212 · Telefax +49 (0) 7836511440
E-Mail: info@hansgrohe.com · Internet: www.hansgrohe.com

03/2006
96141904