


EN Instructions for use / Assembly instructions

DE Gebrauchsanleitung / Montageanleitung

2

3



Varnis Bland 210

71870XX3

**Safety Notes**

- ⚠️ Gloves should be worn during installation to prevent crushing and cutting injuries.
- ⚠️ The hot and cold supplies must be of equal pressures.

Installation Instructions

- Prior to installation, inspect the product for transport damages. After it has been installed, no transport or surface damage will be honoured.
- The pipes and the fixture must be installed, flushed and tested as per the applicable standards.
- The plumbing codes applicable in the respective countries must be observed.

Technical Data

Operating pressure:	max. 1 MPa
Recommended operating pressure:	0,1 - 0,5 MPa
Test pressure:	1,6 MPa

[1 MPa - 10 bar - 145 PSI]

Hot water temperature:	max. 60 °C
Thermal disinfection:	70 °C / 4 min

- The product is exclusively designed for drinking water!
- This product is in compliance with the lead-free requirements of the clause A5G4 of National Construction Code (NCC) 2022 Volume Three - Plumbing Code of Australia.

Symbol description

Do not use silicone containing acetic acid!



Adjustment (see page 6)

To adjust the hot water limiter. Using a hot water limiter in combination with a continuous flow water heater is not recommended.



Dimensions (see page 7)



Flow diagram (see page 7)



Spare parts (see page 8)

- XX - Colors
- 00 - Chrome Plated
- 67 - Matt Black



Cleaning (see page 9)



Operation (see page 9)

Hansgrohe recommends not to use as drinking water the first half liter of water drawn in the morning or after a prolonged period of non-use.

Fault	Cause	Remedy
Mixer wfl	• Cartridge defective, calcified	• Exchange cartridge
Mixer dripping	• Cartridge defective	• Exchange cartridge
Water escaping at the threaded base	• connection hoses not completely screwed into basic body	• Tighten connection hoses by hand
	• O-ring at the connection hose defective	• Exchange O-ring
Hot water temperature too low	• Hot water limiter incorrectly set	• Set hot water limiter



Sicherheitshinweise

- Bei der Montage müssen zur Vermeidung von Quetsch- und Schnittverletzungen Handschuhe getragen werden.
- Große Druckunterschiede zwischen den Kalt- und Warmwasseranschlüssen müssen ausgeglichen werden.

Montagehinweise

- Vor der Montage muss das Produkt auf Transportschäden untersucht werden. Nach dem Einbau werden keine Transport- oder Oberflächenschäden anerkannt.
- Die Leitungen und die Armatur müssen nach den gültigen Normen montiert, gespült und geprüft werden.
- Die in den Ländern jeweils gültigen Installationsrichtlinien sind einzuhalten.

Technische Daten

Betriebsdruck:	max. 1 MPa
Empfohlener Betriebsdruck:	0,1 - 0,5 MPa
Prüfdruck:	1,6 MPa
	(1 MPa - 10 bar - 145 PSI)
Heißwassertemperatur:	max. 60 °C
Thermische Desinfektion:	70 °C / 4 min

- Das Produkt ist ausschließlich für Trinkwasser konzipiert.
- Dieses Produkt entspricht den Anforderungen hinsichtlich Bleifreiheit gemäß Klausel A5G4 des National Construction Code (NCC) 2022, Band 3 - Plumbing Code of Australia (Australischer Sanitärkodex).

Symbolerklärung



Kein essigsäurehaltiges Silikon verwenden!



Justierung (siehe Seite 6)

Einstellen der Warmwasserbegrenzung. In Verbindung mit Durchlauferhitzern ist eine Warmwassersperre nicht zu empfehlen.



Maße (siehe Seite 7)



Durchflussdiagramm
(siehe Seite 7)



Serviceteile (siehe Seite 8)

- XX - Farbcodierung
- 00 - Chrom
- 67 - Mattschwarz



Reinigung (siehe Seite 9)



Bedienung (siehe Seite 9)








Hansgrohe empfiehlt, morgens oder nach längeren Stagnationszeiten den ersten halben Liter nicht als Trinkwasser zu verwenden.



Störung

Ursache

Abhilfe

Armatur schwiegig	• Kartusche defekt, verkalkt	• Kartusche austauschen
Armatur tropft	• Kartusche defekt	• Kartusche austauschen
Wassertritt am Befestigungsort	• Anschlusskläuche nicht ganz in den Grundkörper eingeschraubt • O-Ring am Anschlusslauch defekt	• Anschlusskläuche von Hand festziehen • O-Ring austauschen
Zu niedrige Warmwassertemperatur	• Warmwasserbegrenzung falsch eingestellt	• Warmwasserbegrenzung einstellen













60 °C






10 °C




0,3 MPa









www.hansgrohe.com/cleaning-recommendation



www.hansgrohe.com/warranty



EN Cleaning recommendation / Warranty / Contact

DE Reinigungsempfehlung / Garantie / Kontakt

