

EN Instructions for use / Assembly instructions

DE Gebrauchsanleitung / Montageanleitung

2

3



Ecoc
14430000
14431003




Matris
31454003



Matris
31493003



Focus
31945XX3



Matropol
32545XX3



My Sport
71249000



Logis
71405003



Talis E
71745XX3




Talis S
72405XX3



Rebris S
72466XX3




Rebris E
72468XX3




Matropol
74545003



Zasis S
74415XX3



Vivanis
75415XX3



Finoris
76415XX3

**Safety Notes**

- ⚠️ Gloves should be worn during installation to prevent crushing and cutting injuries.
- ⚠️ The product may only be used for bathing, hygienic and body cleaning purposes.
- ⚠️ Children as well as adults with physical, mental and/or sensoric impairments must not use this product without proper supervision. Persons under the influence of alcohol or drugs are prohibited from using this product.
- ⚠️ The hot and cold supplies must be of equal pressures.

Installation Instructions

- Prior to installation, inspect the product for transport damages. After it has been installed, no transport or surface damage will be honoured.
- The pipes and the fixture must be installed, flushed and tested as per the applicable standards.
- The plumbing codes applicable in the respective countries must be observed.

Technical Data

Operating pressure:	max. 1 MPa
Recommended operating pressure:	0,1 - 0,5 MPa
Test pressure:	1,6 MPa
	11 MPa - 10 bar - 145 PSII
Hot water temperature:	max. 60 °C
Thermal disinfection:	70 °C / 4 min
The product is exclusively designed for drinking water!	

Symbol description

Do not use silicone containing acetic acid!

**Adjustment** (see page 8)

To adjust the hot water limiter. Using a hot water limiter in combination with a continuous flow water heater is not recommended.

**Dimensions** (see page 4)**Flow diagram** (see page 5)

free flow

① Shower outlet

② Tub outlet

**Spare parts** (see page 9)

XX - Colors

00 - Chrome Plated

14 - Brushed Bronze

34 - Brushed Black Chrome

67 - Matt Black

70 - Matt White

82 - Brushed Nickel

99 - Polished Gold-Optic

**Special accessories** (see page 11)

order as an extra

• extension 25 mm #13595000

• Extension Set 22 mm (when wall is not deep enough) #13597000, #13593000, #15597000

**Cleaning** (see page 12)**Operation** (see page 4)

Fault	Cause	Remedy
Mixer stiff	• Cartridge defective, calcified	• Exchange cartridge
Mixer dripping	• Cartridge defective	• Exchange cartridge
Diverter not operating	• Residue	• Clean diverter / grease O-rings
	• Water pressure too low	• Increase water pressure
	• Diverter defective	• Exchange diverter
Hot water temperature too low, no cold water. Instantaneous water heater starts up when cold water is selected.	• Hot water limiter incorrectly set	• Set hot water limiter
	• Crossflow	• Exchange cartridge



Sicherheitshinweise

- Bei der Montage müssen zur Vermeidung von Quetsch- und Schnittverletzungen Handschuhe getragen werden.
- Das Produkt darf nur zu Bade-, Hygiene- und Körperreinigungszwecken eingesetzt werden.
- Kinder, sowie Erwachsene mit körperlichen, geistigen und / oder sensorischen Einschränkungen dürfen das Produkt nicht unbeaufsichtigt benutzen. Personen, die unter Alkoholeinfluss oder Drogeneinfluss stehen, dürfen das Produkt nicht benutzen.
- Große Druckunterschiede zwischen den Kalt- und Warmwasseranschlüssen müssen ausgeglichen werden.

Montagehinweise

- Vor der Montage muss das Produkt auf Transportschäden untersucht werden. Nach dem Einbau werden keine Transport- oder Oberflächenschäden anerkannt.
- Die Leitungen und die Armatur müssen nach den gültigen Normen montiert, gespült und geprüft werden.
- Die in den Ländern jeweils gültigen Installationsrichtlinien sind einzuhalten.

Technische Daten

Betriebsdruck:	max. 1 MPa
Empfohlener Betriebsdruck:	0,1 - 0,5 MPa
Prüfdruck:	1,6 MPa
	11 MPa = 10 bar = 145 PSI
Heißwassertemperatur:	max. 60 °C
Thermische Desinfektion:	70 °C / 4 min
Das Produkt ist ausschließlich für Trinkwasser konzipiert.	

Symbolerklärung



Kein essigsäurehaltiges Silikon verwenden!



Justierung (siehe Seite 8)

Einstellen der Warmwasserbegrenzung. In Verbindung mit Durchlauferhitzer ist eine Warmwasserperiode nicht zu empfehlen.



Maße (siehe Seite 4)



Durchflussdiagramm (siehe Seite 5)

hier: Durchfluss

① Abgang Brause

② Abgang Wanne



Serviceteile (siehe Seite 9)

XX - Farbcodierung

00 - Chrom

14 - Brushed Bronze

34 - Brushed Black Chrome

67 - Mattschwarz

70 - Mattweiß

82 - Brushed Nickel

99 - Polished Gold-Optic



Sonderzubehör (siehe Seite 11)

nicht im Lieferumfang enthalten

• Verlängerung 25 mm #13595000

• Verlängerung 22 mm (bei geringer Einbautiefe) #13597000, #13593000, #15597000



Reinigung (siehe Seite 12)




Bedienung (siehe Seite 4)

Störung	Ursache	Abhilfe
Armatur schwelgig	• Kartusche defekt, verkalkt	• Kartusche austauschen
Armatur tropft	• Kartusche defekt	• Kartusche austauschen
Umsteller funktioniert nicht	• Ablagerungen	• Umsteller reinigen / O-Ringe fetten
	• Zu geringer Wasserdruck	• Wasserdruck erhöhen
	• Umsteller defekt	• Umsteller austauschen
Zu niedrige Warmwassertemperatur, kein Kaltwasser, Durchlauferhitzer springt an, wenn Kaltwasser angewählt wird.	• Warmwasserbegrenzung falsch eingestellt	• Warmwasserbegrenzung einstellen
	• Kreuzfluss	• Kartusche austauschen




Ecós

1443 0000 / 14431003




Matris

31454003




Matris

31493003




Focus

31945XX3




Metropol

32545XX3 / 74545003




MySport

71249000




Logis

71405003




Talis E

71745XX3




Talis S

72405XX3




Rabris S / E

72466XX3 / 72468XX3




Zasis S

74415XX3




Vivaris




75415XX3




Finoris

76415XX3






open / öffnen









close / schließen






hot / warm





cold / kalt





Matris	31454003
Matropol	32545XX3 / 74545003
Logis	71405003
Talis E	71745XX3
Vivanis	75415XX3
Finoris	76415XX3










60 °C



10 °C



0,3 MPa



Ecos

14430000

14431003

Matrís

31493003

Focus

31945XX3

MySport

71249000

Talis S

72405XX3

Rebrís S


72466883

Rabris E

72468XX3

Exsis 5

74415XX3





Matris


314.54.003

Logis

7140.50.03

Talis E


7174.5X.03




Matropol

3254.5X.03

7454.50.03




Vivanis
75415XX3
Finoris
76415XX3



Ecos
14430000
14431003
Matris
31493003
Focus
31945XX3
MySport
71249000



Talis S
72405XX3
Rabris S
72466XX3
Rabris E
72468XX3
Zasis S
74415XX3



Metropol
32545XX3
74545003
Vivanis
75415XX3
Finoris
76415XX3



Matris
31454003
Logis
71405003
Talis E
71745XX3





www.hansgrohe.com/cleaning-recommendation



www.hansgrohe.com/warranty



EN Cleaning recommendation / Warranty / Contact

DE Reinigungsempfehlung / Garantie / Kontakt